

## Saferstep B - 41304

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

### Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Complies with EN 131 Professional.

### Product features

|               |                 |
|---------------|-----------------|
| Anti splay    | Belt strap      |
| Base          | 0,99 m × 0,47 m |
| Certification | TÜV-SÜD         |
| Coating       | anodised        |



|                        |  |
|------------------------|--|
| Connection Stile-Rung  | flanged  |
| Load capacity          | max. 150 kg  |
| Material               | Aluminium  |
| Number of treads       | 4  |
| Number of treads       | 2 × 4  |
| Overall base width     | 0.47 m   |
| Overall length         | 1.16 m   |
| Pitch rung/tread       | 265 mm   |
| Standards              | EN 131 professional                                |
| Stile depth            | 68 mm  |
| Transport dimensions   | approx. 1.160 mm × approx. 470 mm × approx. 215 mm |
| Tread depth            | 80 mm  |
| Type rung/tread        | Safer Step   |
| Vertical ladder height | 1.06 m   |
| Warranty               | 10 years   |
| Weight                 | 6.1 kg   |
| Working height         | 2.55 m   |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 4/5/2026

Subject to change or error.