


Saferstep B - 41305

Safe climbing on both sides, even to great heights on treads featuring Safer-Step technology.

Product description

- Safe climbing on both sides, even to great heights on treads featuring Safer-Step technology.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Clean hands thanks to wear-resistant anodised stiles.
- Sturdy hinges made of die-cast aluminum.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- The 280 mm-high step provides the greatest working height in its class.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Robust design: flanged step-rail connection with extruded aluminum profiles.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|------------|----------------|
| Anti splay | Belt strap |
| Base | 1,18 m × 0,5 m |

| | |
|------------------------|----------------------------------------------------|
| Certification | TÜV-SÜD |
| Coating | anodised |
| Connection Stile-Rung | flanged |
| Load capacity | max. 150 kg |
| Material | Aluminium |
| Number of treads | 5 |
| Number of treads | 2 × 5 |
| Overall base width | 0.5 m |
| Overall length | 1.44 m |
| Pitch rung/tread | 265 mm |
| Standards | EN 131 professional |
| Stile depth | 68 mm |
| Transport dimensions | approx. 1.440 mm × approx. 500 mm × approx. 215 mm |
| Tread depth | 80 mm |
| Type rung/tread | Safer Step |
| Vertical ladder height | 1.32 m |
| Warranty | 10 years |
| Weight | 7.6 kg |
| Working height | 2.8 m |

ZARGES GmbH

Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 7/1/2026

Subject to change or error.