

## Saferstep B - 41307

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

## **Product description**

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- · Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Maximum working heights thanks to 280mm high access.







## Hints and special features

Complies with EN 131 Professional.

## **Product features**

Anti splay  Belt strap	Base 1,58 m × 0,56 m	Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg
Material <b>Aluminium</b>	Number of treads	Number of treads 2 × 7	Overall base width  0.56 m	Overall length  1.98 m

ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 www.zarges.com zarges@zarges.de



Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth
265 mm	EN 131 professional	68 mm	1.985 mm × 565 mm × 230 mm	80 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
Safer Step	1.84 m	10 years	10.9 kg	3.3 m

82362 Weilheim