

Saferstep B - 41307

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|---------------|-----------------|
| Anti splay | Belt strap |
| Base | 1,58 m × 0,56 m |
| Certification | TÜV-SÜD |
| Coating | anodised |



| | |
|------------------------|--|
| Connection Stile-Rung | flanged |
| Load capacity | max. 150 kg |
| Material | Aluminium |
| Number of treads | 7 |
| Number of treads | 2 × 7 |
| Overall base width | 0.56 m |
| Overall length | 2 m |
| Pitch rung/tread | 265 mm |
| Standards | EN 131 professional |
| Stile depth | 68 mm |
| Transport dimensions | approx. 2.000 mm × approx. 560 mm × approx. 215 mm |
| Tread depth | 80 mm |
| Type rung/tread | Safer Step |
| Vertical ladder height | 1.84 m |
| Warranty | 10 years |
| Weight | 10.9 kg |
| Working height | 3.3 m |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 4/6/2026

Subject to change or error.