

Saferstep B - 41308

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	1,77 m × 0,58 m
Certification	TÜV-SÜD
Coating	anodised



Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of treads	8
Number of treads	2 × 8
Overall base width	0.58 m
Overall length	2.27 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	2.275 mm × approx. 580 mm × approx. 215 mm
Tread depth	80 mm
Type rung/tread	Safer Step
Vertical ladder height	2.1 m
Warranty	10 years
Weight	12.7 kg
Working height	3.6 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 4/6/2026

Subject to change or error.