

Saferstep B - 41310

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Maximum working heights thanks to 280mm high access.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
Belt strap	2,16 m x 0,65 m	anodised	flanged	max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length
Aluminium	10	2 x 10	0.65 m	2.83 m



ZARGES

Pitch rung/tread 265 mm	Standards EN 131 professional	Stile depth 68 mm	Transport dimensions 2.835 mm × 655 mm × 230 mm	Tread depth 80 mm
Type rung/tread Safer Step	Vertical ladder height 2.62 m	Warranty 10 years	Weight 16.4 kg	Working height 4.15 m

certification-mark-pf

TÜV-SÜD

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

www.zarges.com

zarges@zarges.de

Effective
2/11/2026

Subject to change or error.

2/2