

Saferstep B - 41312

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Maximum working heights thanks to 280mm high access.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
Belt strap	2,55 m x 0,71 m	anodised	flanged	max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length
Aluminium	12	2 x 12	0.71 m	3.39 m



Pitch rung/tread 265 mm	Standards EN 131 professional	Stile depth 68 mm	Transport dimensions 3.390 mm × 715 mm × 230 mm	Tread depth 80 mm
Type rung/tread Safer Step	Vertical ladder height 3.15 m	Warranty 10 years	Weight 20.3 kg	Working height 4.65 m
certification-mark-pf				TÜV-SÜD