


Saferstep L - 41362

The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.

Product description

- The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.
- Also available as a shelf-ladder.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Overall width: 420 mm.
- High strength, non-twist rung/stile connections.
- Treads and stiles made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium	Number of treads 12
----------------------------	---	-------------------------------------	------------------------------	-------------------------------



Overall length 3.62 m	Pitch rung/tread 265 mm	Standards EN 131 professional	Stile depth 68 mm	Transport dimensions 3.610 mm × 420 mm × approx. 80 mm
Tread depth 80 mm	Type rung/tread Safer Step	Warranty 10 years	Weight 10.3 kg	Wide crosspiece 0.8 m
Working height 4.4 m				