


Saferstep L - 41362

The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.

Product description

- The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.
- Also available as a shelf-ladder.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Overall width: 420 mm.
- High strength, non-twist rung/stile connections.
- Treads and stiles made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|----------------------------|---|-------------------------------------|------------------------------|-------------------------------|
| Coating anodised | Connection Stile-Rung flanged | Load capacity max. 150 kg | Material Aluminium | Number of treads 12 |
|----------------------------|---|-------------------------------------|------------------------------|-------------------------------|

| | | | | |
|---------------------------------|---|---|-----------------------------|--|
| Overall length 3.62 m | Pitch rung/tread 265 mm | Standards EN 131 professional | Stile depth 68 mm | Transport dimensions 3.610 mm × 420 mm × approx. 80 mm |
| Tread depth 80 mm | Type rung/tread Safer Step | Warranty 10 years | Weight 10.3 kg | Wide crosspiece 0.8 m |
| Working height 4.4 m | certification-mark-pf TÜV-SÜD | | | |