

## Saferstep S - 41374

Comfortable and safe ascent with high non-slip performance thanks to Safer Step Technology and robust, stable construction.

### Product description

- Comfortable and safe ascent with high non-slip performance thanks to Safer Step Technology and robust, stable construction.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Practical tray with plenty of space for tools and small items.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Practical aluminium storage tray for small items and tools.
- Platform made from extruded aluminium (300 mm x 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features



Complies with EN 131 Professional.

## Product features

Base <b>0,91 m × 0,52 m</b>	Coating <b>anodised</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Number of rungs, incl. platform <b>4</b>	Overall base width <b>0.52 m</b>	Overall length <b>1.87 m</b>	Pitch rung/tread <b>265 mm</b>	Platform height <b>1.06 m</b>
Platform length <b>250 mm</b>	Platform width <b>300 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>68 mm</b>	Stile depth <b>48 mm</b>
Stile depth steps/back stay <b>68mm / 48mm</b>	Transport dimensions <b>approx. 1.880 mm × approx. 520 mm × approx. 230 mm</b>	Tray <b>Aluminium</b>	Tread depth <b>80 mm</b>	Type rung/tread <b>Safer Step</b>
Warranty <b>10 years</b>	Weight <b>7.6 kg</b>	Working height <b>3.1 m</b>	certification-mark-pf <b>TÜV-SÜD</b>	