

Saferstep S - 41376

Comfortable and safe ascent with high non-slip performance thanks to Safer Step Technology and robust, stable construction.

Product description

- Comfortable and safe ascent with high non-slip performance thanks to Safer Step Technology and robust, stable construction.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Practical tray with plenty of space for tools and small items.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Practical aluminium storage tray for small items and tools.
- Platform made from extruded aluminium (300 mm x 250 mm) for safe and comfortable standing even when working for longer periods of time.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.





Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|-------------------|---------------------------------|---|----------------------------|-----------------------|
| Anti splay | Base | Coating | Connection Stile-Rung | Load capacity |
| Belt strap | 1,25 m × 0,58 m | anodised | flanged | max. 150 kg |
| Material | Number of rungs, incl. platform | Overall base width | Overall length | Pitch rung/tread |
| Aluminium | 6 | 0.58 m | 2.43 m | 265 mm |
| Platform height | Platform length | Platform width | Standards | Stile depth |
| 1.59 m | 250 mm | 300 mm | EN 131 professional | 68 mm |
| Stile depth | Stile depth steps/back stay | Transport dimensions | Tray | Tread depth |
| 48 mm | 68mm / 48mm | approx. 2.430 mm × approx. 580 mm × 230 mm | Aluminium | 80 mm |
| Type rung/tread | Warranty | Weight | Working height | certification-mark-pf |
| Safer Step | 10 years | 9.9 kg | 3.6 m | TÜV-SÜD |