DATA SHEET

Roof ladders - 41395

Safe access to various roof pitches via high-stability stationary ladder with rungs arranged eccentrically.



PRODUCT DESCRIPTION

- Safe access to various roof pitches via high-stability stationary ladder with rungs arranged eccentrically.
- Safe, square rungs with 2 differently inclined tread surfaces.
- Robust stile sections ensure 80 mm safety clearance between the rungs and the roof surface.
- Problem-free coordination of the ladder to the relevant roof length.
- Off-centre rung arrangement.
- Maximum loading capacity 150 kg.
- Outside width: 340 mm.
- High strength, non-twist rung/stile connections.
- Rungs made from extruded aluminium sections for maximum safety.

HINTS AND SPECIAL FEATURES

Connecting straps are included with every roof ladder as standard.

PRODUCT FEATURES

Property	Value
Coating	powder-coated
Colour	Anthracite grey
Connection Stile-Rung	flanged
Ladder width	340 mm

Property	Value
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	7
Overall length	2 m
Pitch rung/tread	280 mm
Stile depth	110 mm
Transport dimensions	2.000 mm × 340 mm × 110 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	3.2 kg

ACCESSORIES AND SPARE PARTS

ACCESSORIES 6



Lock for roof ladder safety hooks
SKU 41695



Mobile ridge hook
SKU 40980



Roof safety hooks to DIN EN 517
SKU 40969



Roof safety hooks to DIN EN 517
SKU 41399



Roof safety hooks to DIN EN 517
SKU 41386



Roof safety hooks to DIN EN 517
SKU 41389

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/13/2026
Subject to change or error.