

# Comfortstep S - 41424

Protection for your shins: high degree of comfort while working through padded treads.

## Product description

- Protection for your shins: high degree of comfort while working through padded treads.
- Deep treads with padded front edge for standing comfort.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Practical aluminium storage tray for small items and tools.
- High-strength perlon belts prevent splay.
- Treads with plastic-cushioned front edges.
- Screwed connection between treads and stile.
- Treads and stiles made from extruded aluminium sections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

|  |   |   |   |                                     |
|--|---|---|---|-------------------------------------|
| Anti splay<br><b>Belt strap</b>                        | Base<br><b>1,27 m × 0,59 m</b>                    | Coating<br><b>anodised</b>                                | Connection Stile-Rung<br><b>bolted</b>  | Load capacity<br><b>max. 150 kg</b> |
| Material<br><b>Aluminium</b>                           | Number of rungs, incl. platform<br><b>6</b>       | Overall base width<br><b>0.59 m</b>                       | Overall length<br><b>2.33 m</b>         | Pitch rung/tread<br><b>250 mm</b>   |
| Platform height<br><b>1.5 m</b>                        | Platform length<br><b>250 mm</b>                  | Platform width<br><b>300 mm</b>                           | Standards<br><b>EN 131 professional</b> | Stile depth<br><b>48 mm</b>         |
| Stile depth<br><b>42 mm</b>                            | Stile depth steps/back stay<br><b>48mm / 42mm</b> | Transport dimensions<br><b>2.330 mm × 590 mm × 150 mm</b> | Tray<br><b>Aluminium</b>                | Tread depth<br><b>80 mm</b>         |
| Type rung/tread<br><b>padding on front tread edges</b> | Vertical ladder height<br><b>2.13 m</b>           | Warranty<br><b>10 years</b>                               | Weight<br><b>9.7 kg</b>                 | Working height<br><b>3.5 m</b>      |
| certification-mark-pf<br><b>TÜV-SÜD</b>                |   |   |   |                                     |