

## Comfortstep S - 41427

Protection for your shins: high degree of comfort while working through padded treads.

### Product description

- Protection for your shins: high degree of comfort while working through padded treads.
- Deep treads with padded front edge for standing comfort.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm x 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Practical aluminium storage tray for small items and tools.
- High-strength perlon belts prevent splay.
- Treads with plastic-cushioned front edges.
- Screwed connection between treads and stile.
- Treads and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features



Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
<b>Belt strap</b>	<b>1,95 m x 0,7 m</b>	<b>anodised</b>	<b>bolted</b>	<b>max. 150 kg</b>
Material	Number of rungs, incl. platform	Overall base width	Overall length	Pitch rung/tread
<b>Aluminium</b>	<b>10</b>	<b>0.7 m</b>	<b>3.4 m</b>	<b>250 mm</b>
Platform height	Platform length	Platform width	Standards	Stile depth
<b>2.5 m</b>	<b>250 mm</b>	<b>300 mm</b>	<b>EN 131 professional</b>	<b>48 mm</b>
Stile depth	Stile depth steps/back stay	Transport dimensions	Tray	Tread depth
<b>42 mm</b>	<b>48mm / 42mm</b>	<b>3.410 mm x 700 mm x 150 mm</b>	<b>Aluminium</b>	<b>80 mm</b>
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
<b>padding on front tread edges</b>	<b>3.13 m</b>	<b>10 years</b>	<b>14.4 kg</b>	<b>4.5 m</b>
certification-mark-pf				
<b>TÜV-SÜD</b>				