

## Comfortstep B - 41430

Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.

### Product description

- Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.
- Deep treads with padded front edge for standing comfort.
- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Treads with plastic-cushioned front edges.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.
- Screwed connection between treads and stile.



### Hints and special features

Maximum comfort due to padded treads.

Complies with EN 131 Professional.

### Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
<b>Belt strap</b>	<b>2,36 m x 0,68 m</b>	<b>anodised</b>	<b>bolted</b>	<b>max. 150 kg</b>
Material	Number of treads	Number of treads	Overall base width	Overall length



<b>Aluminium</b>	<b>11</b>	<b>2 × 11</b>	<b>0.68 m</b>	<b>2.99 m</b>
Pitch rung/tread <b>250 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>48 mm</b>	Transport dimensions <b>3.000 mm × 680 mm × 174 mm</b>	Tread depth <b>80 mm</b>
Type rung/tread <b>padding on front tread edges</b>	Vertical ladder height <b>2.75 m</b>	Warranty <b>10 years</b>	Weight <b>17.6 kg</b>	Working height <b>4.25 m</b>
certification-mark-pf				<b>TÜV-SÜD</b>