

Comfortstep B - 41432

Padded front edges on the steps protect your shins and make working at heights for extended periods much more comfortable.

Product description

- Padded front edges on the steps protect your shins and make working at heights for extended periods much more comfortable.
- Deep treads with padded front edge for standing comfort.
- 80 mm deep treads with a padded front edge protect the shins.
- Non-slip two-component ladder feet with a large contact surface.
- Clean hands thanks to wear-resistant anodised stiles.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Durable design for everyday use: extruded aluminum profiles.
- Screwed connection between treads and stile.



Hints and special features

Maximum comfort due to padded treads.

Complies with EN 131 Professional.

Product features

Anti splay

Belt strap



Base	0,75 m × 0,45 m
Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	bolted
Load capacity	max. 150 kg
Material	Aluminium
Number of treads	3
Number of treads	2 × 3
Overall base width	0.45 m
Overall length	0.84 m
Pitch rung/tread	250 mm
Standards	EN 131 professional
Stile depth	42 mm
Transport dimensions	840 mm × approx. 450 mm × 174 mm
Tread depth	80 mm
Type rung/tread	padding on front tread edges
Vertical ladder height	0.75 m
Warranty	10 years
Weight	4.4 kg
Working height	2.25 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/27/2026

Subject to change or error.