

## Comfortstep B - 41433

Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.

## **Product description**

- Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.
- Deep treads with padded front edge for standing comfort.
- 80 mm deep treads with padded front edges.
- · Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Treads with plastic-cushioned front edges.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.
- Screwed connection between treads and stile.

## Hints and special features

Maximum comfort due to padded treads.

Complies with EN 131 Professional.

## **Product features**

Anti splay  Belt strap	Base 0,95 m × 0,47 m	Coating anodised	Connection Stile-Rung bolted	Load capacity max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length







ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 www.zarges.com zarges@zarges.de

Effective 12/5/2025

82362 Weilheim Subject to change or error.



Aluminium	4	2 × 4	0.47 m	1.11 m
Pitch rung/tread 250 mm	Standards EN 131 professional	Stile depth 42 mm	Transport dimensions  1.110 mm × 470 mm  × 174 mm	Tread depth 80 mm
Type rung/tread  padding on front tread edges	Vertical ladder height  1 m	Warranty  10 years	Weight 5.8 kg	Working height  2.5 m

82362 Weilheim