

Comfortstep B - 41435

Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.

Product description

- Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.
- Deep treads with padded front edge for standing comfort.
- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Treads with plastic-cushioned front edges.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.
- Screwed connection between treads and stile.



Hints and special features

Maximum comfort due to padded treads.

Complies with EN 131 Professional.

Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
Belt strap	1,35 m x 0,53 m	anodised	bolted	max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length



Aluminium	6	2 × 6	0.53 m	1.65 m
Pitch rung/tread 250 mm	Standards EN 131 professional	Stile depth 42 mm	Transport dimensions 1.650 mm × 530 mm × 174 mm	Tread depth 80 mm
Type rung/tread padding on front tread edges	Vertical ladder height 1.5 m	Warranty 10 years	Weight 8.8 kg	Working height 3 m
certification-mark-pf				TÜV-SÜD