

Comfortstep B - 41437

Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.

Product description

- Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.
- Deep treads with padded front edge for standing comfort.
- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Treads with plastic-cushioned front edges.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.
- Screwed connection between treads and stile.



Hints and special features

Maximum comfort due to padded treads.

Complies with EN 131 Professional.

Product features

| | | | | |
|-------------------|------------------------|------------------|-----------------------|--------------------|
| Anti splay | Base | Coating | Connection Stile-Rung | Load capacity |
| Belt strap | 1,75 m × 0,59 m | anodised | bolted | max. 150 kg |
| Material | Number of treads | Number of treads | Overall base width | Overall length |

| | | | | |
|--|---|-----------------------------|---|--------------------------------|
| Aluminium | 8 | 2 × 8 | 0.59 m | 2.18 m |
| Pitch rung/tread 250 mm | Standards EN 131 professional | Stile depth 48 mm | Transport dimensions 2.185 mm × 590 mm × 174 mm | Tread depth 80 mm |
| Type rung/tread padding on front tread edges | Vertical ladder height 2 m | Warranty 10 years | Weight 12.2 kg | Working height 3.5 m |