

Skymaster X - 41537

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	Ladder length as 3-part single ladder 5 m	Length as 2-part single ladder and as stepladder with push-on section	Load capacity max. 150 kg
---------------------------	---	---	---	-------------------------------------

			3.6 m	
Material Aluminium	Number of rungs 7	Number of rungs 3 × 7	Overall length, retracted 2.2 m	Pitch rung/tread 265 mm
Rigid locking bar on one side	Standards EN 131 professional	Stile depth 68 mm	Transport dimensions 2.160 mm × 500 mm × 180 mm	Tread depth 30 mm
Type rung/tread serrated	Warranty 10 years	Weight 15 kg	Wide crosspiece 0.9 m	Working height as 3- part single ladder 5.8 m
certification-mark-pf TÜV-SÜD				