

Skymaster X - 41538

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Can be used on steps / stairs.
- Upper ladder can also be used separately as single ladders.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features



Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Ladder length as 3-part single ladder	5.8 m
Length as 2-part single ladder and as stepladder with push-on section	4.1 m
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	8
Number of rungs	3 × 8
Overall length, retracted	2.45 m
Pitch rung/tread	265 mm
Rigid locking bar	on one side
Standards	EN 131 professional
Stile depth	73 mm
Transport dimensions	2.440 mm × 500 mm × 200 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	17.5 kg
Wide crosspiece	1 m
Working height as 3-part single ladder	6.65 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/22/2026

Subject to change or error.