



ZARGES

## Skymaster X - 41540

Convertible to take on challenging tasks with greater safety.

### Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Can be used on steps / stairs.
- Upper ladder can also be used separately as single ladders.
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[www.zarges.com](http://www.zarges.com)

[zarges@zarges.de](mailto:zarges@zarges.de)

Effective  
2/11/2026

Subject to change or error.

1/2



Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Ladder length as 3-part single ladder <b>6.9 m</b>	Length as 2-part single ladder and as stepladder with push-on section <b>4.95 m</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs <b>10</b>	Number of rungs <b>3 × 10</b>	Overall length, retracted <b>3 m</b>	Pitch rung/tread <b>265 mm</b>
Rigid locking bar <b>on one side</b>	Standards <b>EN 131 professional</b>	Stile depth <b>85 mm</b>	Transport dimensions <b>3.010 mm × 500 mm × 210 mm</b>	Tread depth <b>30 mm</b>
Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	Weight <b>25.2 kg</b>	Wide crosspiece <b>1.1 m</b>	Working height as 3-part single ladder <b>7.7 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				