



ZARGES

Skymaster X - 41542

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Cannot be used on stairs.
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection Stile-Rung	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-	Load capacity
---------	-----------------------	---------------------------------------	---	---------------

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

www.zarges.com

zarges@zarges.de

Effective
2/11/2026

Subject to change or error.

1/2



natural	flanged	8.6 m	on section 6.1 m	max. 150 kg
Material	Number of rungs	Number of rungs	Overall length, retracted	Pitch rung/tread
Aluminium	12	3 × 12	3.55 m	265 mm
Rigid locking bar on one side	Standards EN 131 professional	Stile depth 98 mm	Transport dimensions 3.590 mm × 500 mm × 230 mm	Tread depth 30 mm
Type rung/tread serrated	Warranty 10 years	Weight 30.1 kg	Wide crosspiece 1.2 m	Working height as 3-part single ladder 9.35 m
certification-mark-pf TÜV-SÜD				