

# Skymaster X - 41542

Convertible to take on challenging tasks with greater safety.

## Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Cannot be used on stairs.
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Certification	TÜV-SÜD
Coating	natural



Connection Stile-Rung	flanged
Ladder length as 3-part single ladder	8.6 m
Length as 2-part single ladder and as stepladder with push-on section	6.1 m
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	12
Number of rungs	3 × 12
Overall length, retracted	3.55 m
Pitch rung/tread	265 mm
Rigid locking bar	on one side
Standards	EN 131 professional
Stile depth	98 mm
Transport dimensions	3.590 mm × 500 mm × 230 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	30.1 kg
Wide crosspiece	1.2 m
Working height as 3-part single ladder	9.35 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 4/5/2026

Subject to change or error.