

Skymaster X - 41542

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Cannot be used on stairs.
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection Stile-Rung	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-	Load capacity
---------	-----------------------	---------------------------------------	---	---------------

natural	flanged	8.6 m	on section 6.1 m	max. 150 kg
Material Aluminium	Number of rungs 12	Number of rungs 3 × 12	Overall length, retracted 3.55 m	Pitch rung/tread 265 mm
Rigid locking bar on one side	Standards EN 131 professional	Stile depth 98 mm	Transport dimensions 3.590 mm × 500 mm × 230 mm	Tread depth 30 mm
Type rung/tread serrated	Warranty 10 years	Weight 30.1 kg	Wide crosspiece 1.2 m	Working height as 3-part single ladder 9.35 m