

## Skymaster X - 41544

Convertible to take on challenging tasks with greater safety.

## **Product description**

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos.
   41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- · Cannot be used on stairs.
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.

## Hints and special features

Complies with EN 131 Professional.

## **Product features**

Coating Connection Stile-Rung

Ladder length as 3-part single ladder

Length as 2-part single ladder and as stepladder with pushLoad capacity











ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 www.zarges.com zarges@zarges.de

Effective 11/4/2025

82362 Weilheim Subject to change or error.



natural	flanged	9.7 m	on section 6.95 m	max. 150 kg
Material  Aluminium	Number of rungs	Number of rungs 3 × 14	Overall length, retracted 4.15 m	Pitch rung/tread 265 mm
Rigid locking bar  on one side	Standards EN 131 professional	Stile depth 98 mm	Transport dimensions 4.140 mm × 500 mm × 230 mm	Tread depth 30 mm
Type rung/tread serrated	Warranty  10 years	Weight 37.9 kg	Wide crosspiece  1.2 m	Working height as 3- part single ladder 10.4 m

82362 Weilheim