

## Alto L - 41547

The compact alternative - with respect to size, weight and price/performance ratio.

### Product description

- The compact alternative - with respect to size, weight and price/performance ratio.
- Very light but still extremely stable.
- Rung depth: 30 mm
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	7
Overall length	2.21 m
Pitch rung/tread	270 mm



Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	2.210 mm × 350 mm × 60 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	4 kg
Working height	3.05 m
certification-mark-pf	TÜV-SÜD

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 3/29/2026

Subject to change or error.