

R13step B - 41553

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 tread and grooves, as well as perforations to allow liquids to drain, for noticeably better traction in any situation.
- Clean hands thanks to wear-resistant anodised stiles.
- Sturdy hinges made of die-cast aluminum.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- The 280 mm-high step provides the greatest working height in its class.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Robust design: flanged step-rail connection with extruded aluminum profiles.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	1,18 m × 0,5 m

Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of treads	5
Number of treads	2 × 5
Overall base width	0.5 m
Overall length	1.44 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	approx. 1.440 mm × approx. 500 mm × approx. 220 mm
Tread depth	80 mm
Type rung/tread	R13 tread
Vertical ladder height	1.32 m
Warranty	10 years
Weight	8.3 kg
Working height	2.8 m

ZARGES GmbH

Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 7/2/2026

Subject to change or error.