


# R13step B - 41553

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

## Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
<b>Belt strap</b>	<b>1,18 m x 0,5 m</b>	<b>anodised</b>	<b>flanged</b>	<b>max. 150 kg</b>
Material	Number of treads	Number of treads	Overall base width	Overall length
<b>Aluminium</b>	<b>5</b>	<b>2 x 5</b>	<b>0.5 m</b>	<b>1.42 m</b>
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth



ZARGES

265 mm	EN 131 professional	73 mm	approx. 1.440 mm x approx. 500 mm x approx. 220 mm	80 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
R13 tread	1.32 m	10 years	8.4 kg	2.8 m

certification-mark-pf  
TÜV-SÜD

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[www.zarges.com](http://www.zarges.com)

[zarges@zarges.de](mailto:zarges@zarges.de)

Effective  
2/12/2026

Subject to change or error.

2/2