

## Alto L - 41556

The compact alternative—in terms of both size and weight, as well as price/performance.

### Product description

- The compact alternative—in terms of both size and weight, as well as price/performance.
- Very light but still extremely stable.
- Rung depth: 30 mm
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	16
Overall length	4.73 m



Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	4.730 mm × 350 mm × 70 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	9.2 kg
Wide crosspiece	0.89 m
Working height	5.5 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 6/20/2026

Subject to change or error.