

R13step B - 41557

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 tread and grooves, as well as perforations to allow liquids to drain, for noticeably better traction in any situation.
- Clean hands thanks to wear-resistant anodised stiles.
- Sturdy hinges made of die-cast aluminum.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- The 280 mm-high step provides the greatest working height in its class.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Robust design: flanged step-rail connection with extruded aluminum profiles.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|------------|-----------------|
| Anti splay | Belt strap |
| Base | 1,57 m × 0,56 m |



ZARGES

| | |
|------------------------|--|
| Certification | TÜV-SÜD |
| Coating | anodised |
| Connection Stile-Rung | flanged |
| Load capacity | max. 150 kg |
| Material | Aluminium |
| Number of treads | 7 |
| Number of treads | 2 × 7 |
| Overall base width | 0.56 m |
| Overall length | 1.99 m |
| Pitch rung/tread | 265 mm |
| Standards | EN 131 professional |
| Stile depth | 68 mm |
| Transport dimensions | approx. 2.000 mm × approx. 560 mm × approx. 220 mm |
| Tread depth | 80 mm |
| Type rung/tread | R13 tread |
| Vertical ladder height | 1.84 m |
| Warranty | 10 years |
| Weight | 11 kg |
| Working height | 3.3 m |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 7/2/2026

Subject to change or error.