


R13step B - 41559

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Base 1,77 m × 0,59 m	Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg
Material Aluminium	Number of treads 8	Number of treads 2 × 8	Overall base width 0.59 m	Overall length 2.27 m
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth



ZARGES

265 mm	EN 131 professional	73 mm	approx. 2.280 mm × approx. 590 mm × approx. 220 mm	80 mm
Type rung/tread R13 tread	Vertical ladder height 2.1 m	Warranty 10 years	Weight 11.5 kg	Working height 3.6 m