

R13step B - 41563

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	2,55 m × 0,71 m
Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium



Number of treads	12
Number of treads	2 × 12
Overall base width	0.71 m
Overall length	3.39 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	73 mm
Transport dimensions	approx. 3.390 mm × approx. 710 mm × approx. 220 mm
Tread depth	80 mm
Type rung/tread	R13 tread
Vertical ladder height	3.15 m
Warranty	10 years
Weight	17.8 kg
Working height	4.65 m
certification-mark-pf	TÜV-SÜD

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 3/29/2026

Subject to change or error.