

## Skymaster Plus X - 41579

One ladder, many functions: the flexible solution for accessing higher places safely and providing extra stability. The ladder is particularly safe and comfortable to use due to the 80 mm deep treads on the upper ladder.

### Product description

- One ladder, many functions: the flexible solution for accessing higher places safely and providing extra stability. The ladder is particularly safe and comfortable to use due to the 80 mm deep treads on the upper ladder.
- Particularly light thanks to the combination of stepladder and rung ladder (hybrid design).
- Maximum stability thanks to rigid connection on both sides.
- The horizontal stabiliser bar is fitted with castors for ergonomic transport.
- Upper ladder with top wheel assembly.
- Upper ladder can also be used separately as single ladders for Order Nos. 41578-41579.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



## Hints and special features

Optimum stability due to extra-wide horizontal stabiliser bar and two rigid locking bars.

Complies with EN 131 Professional.

## Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Ladder length as 3-part single ladder	6.88 m
Length as 2-part single ladder and as stepladder with push-on section	4.94 m
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	10
Number of rungs	3 × 10
Overall length, retracted	3.01 m
Pitch rung/tread	265 mm
Rigid locking bar	on both sides
Standards	EN 131 professional
Stile depth	85 mm
Transport dimensions	approx. 3.015 mm × approx. 500 mm × approx. 230 mm
Type rung/tread	serrated
Warranty	10 years



Weight 26.2 kg

Wheels Rubber

Wide crosspiece 1.185 m

Working height as 3-part single ladder max. approx. 7.6 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 6/27/2026

Subject to change or error.