



## Meistertritt S - 41635

Safe standing on very large platform, non-slip ascent and descent thanks to Safer Step Technology. So-called "lightweight platform ladder".

### Product description

- Safe standing on very large platform, non-slip ascent and descent thanks to Safer Step Technology. So-called "lightweight platform ladder".
- Particularly large work platform with ribbed aluminium sheet covering.
- With two handrails as standard for safe access.
- 80 mm deep steps with ZARGES Safer Step Technology for fatigue-free standing.
- Particularly large-surface work platform with ribbed aluminium sheet lining (approx. 380 x 390 mm).
- Practical aluminium storage tray for small items and tools.
- High-strength perlon belts prevent splay.
- Height of the retaining bracket 1,000 mm.
- Treads and stiles made from extruded aluminium sections.



### Hints and special features

Mobile version from 5 steps possible.

Complies with EN 131 Professional.

### Product features



|                       |                                 |                                   |                            |                    |
|-----------------------|---------------------------------|-----------------------------------|----------------------------|--------------------|
| Anti splay            | Base                            | Coating                           | Connection Stile-Rung      | Load capacity      |
| <b>Belt strap</b>     | <b>2,46 m x 0,86 m</b>          | <b>natural</b>                    | <b>flanged</b>             | <b>max. 150 kg</b> |
| Material              | Number of rungs, incl. platform | Overall base width                | Overall length             | Pitch rung/tread   |
| <b>Aluminium</b>      | <b>12</b>                       | <b>0.86 m</b>                     | <b>4.44 m</b>              | <b>265 mm</b>      |
| Platform height       | Platform length                 | Platform width                    | Standards                  | Stile depth        |
| <b>3.11 m</b>         | <b>380 mm</b>                   | <b>390 mm</b>                     | <b>EN 131 professional</b> | <b>73 mm</b>       |
| Stile depth           | Stile depth steps/back stay     | Transport dimensions              | Tray                       | Tread depth        |
| <b>58 mm</b>          | <b>73mm / 58mm</b>              | <b>4.440 mm x 860 mm x 155 mm</b> | <b>Aluminium</b>           | <b>80 mm</b>       |
| Type rung/tread       | Vertical ladder height          | Warranty                          | Weight                     | Working height     |
| <b>Safer Step</b>     | <b>4.11 m</b>                   | <b>10 years</b>                   | <b>23.3 kg</b>             | <b>5.1 m</b>       |
| certification-mark-pf |                                 |                                   |                            |                    |
| <b>TÜV-SÜD</b>        |                                 |                                   |                            |                    |