

R13step S - 41636

Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.

Product description

- Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.
- Large platform with R13 surface that allows personnel to stand safely and comfortably even when working for extended periods.
- Spacious aluminium storage tray for material and tools.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Platform and treads with R13 surface.

Complies with EN 131 Professional.

Product features

Base	0,74 m × 0,49 m
Certification	TÜV-SÜD
Coating	anodised



Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs, incl. platform	3
Overall base width	0.49 m
Overall length	1.59 m
Pitch rung/tread	265 mm
Platform height	0.8 m
Platform length	250 mm
Platform width	300 mm
Standards	EN 131 professional
Stile depth	68 mm
Stile depth	58 mm
Stile depth steps/back stay	68mm / 58mm
Transport dimensions	approx. 1.590 mm × approx. 490 mm × approx. 170 mm
Tray	Aluminium
Tread depth	80 mm
Type rung/tread	R13 tread
Warranty	10 years
Weight	8.3 kg
Working height	2.8 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 4/14/2026

Subject to change or error.