

R13step S - 41638

Stable footing even in wet or oily conditions: on R13 treads when going up and down, as well as on the extra-wide platform.

Product description

- Stable footing even in wet or oily conditions: on R13 treads when going up and down, as well as on the extra-wide platform.
- The widest platform in its class, featuring an R13-rated surface for a non-slip, comfortable stance even during extended use.
- Spacious aluminum storage tray with plenty of room for tools and small parts.
- 80 mm deep treads with R13 tread and grooves, as well as perforations to allow liquids to drain, for noticeably better traction in any situation.
- Clean hands thanks to wear-resistant anodised stiles.
- The 280 mm-high step provides the greatest working height in its class.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Robust design: flanged step-stile connection with a platform and extruded aluminum profiles.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Platform and treads with R13 surface.

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	1,09 m × 0,55 m
Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs, incl. platform	5
Overall base width	0.55 m
Overall length	2.15 m
Pitch rung/tread	265 mm
Platform height	1.33 m
Platform length	250 mm
Platform width	300 mm
Standards	EN 131 professional
Stile depth	68 mm
Stile depth	58 mm
Stile depth steps/back stay	68mm / 58mm
Transport dimensions	approx. 2.150 mm × approx. 550 mm × approx. 170 mm



Tray Aluminium

Tread depth 80 mm

Type rung/tread R13 tread

Warranty 10 years

Weight 10.5 kg

Working height 3.35 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/29/2026

Subject to change or error.