

## R13step S - 41639

Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.

### Product description

- Safer ascent with the highest non-slip performance thanks to R13 treads for oily and wet environment.
- Large platform with R13 surface that allows personnel to stand safely and comfortably even when working for extended periods.
- Spacious aluminium storage tray for material and tools.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Maximum working heights thanks to 280mm high access.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Platform and treads with R13 surface.

Complies with EN 131 Professional.

### Product features

Anti splay	Belt strap
Base	1,25 m × 0,58 m



Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs, incl. platform	6
Overall base width	0.58 m
Overall length	2.43 m
Pitch rung/tread	265 mm
Platform height	1.59 m
Platform length	250 mm
Platform width	300 mm
Standards	EN 131 professional
Stile depth	68 mm
Stile depth	58 mm
Stile depth steps/back stay	68mm / 58mm
Transport dimensions	approx. 2.430 mm × approx. 580 mm × approx. 170 mm
Tray	Aluminium
Tread depth	80 mm
Type rung/tread	R13 tread
Warranty	10 years
Weight	11.5 kg



Working height

3.6 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 4/14/2026

Subject to change or error.