

ZAP Safemaster S - 41675

Safe ascent and descent due to non-slip treads and handrail, high degree of stability and compact transport dimensions.

Product description

- Safe ascent and descent due to non-slip treads and handrail, high degree of stability and compact transport dimensions.
- Optimum stability thanks to rigid locking bar on both sides.
- Foldable anodised handrails allow it to take up less space during transport.
- The handle on the platform allows the ladder to be folded up quickly and effortlessly.
- Extra-large work platform (400 x 400 mm).
- Anodised handrails and guardrails.
- Generously sized storage tray for tools and small parts.
- Treads 80 mm deep, with ZARGES Safer Step Technology.
- Can be retrofitted with optional stabiliser sets to comply with EN 131, Part 7.



Product features

Anti splay	Rigid locking bar
Certification	TÜV-SÜD
Guardrail height	1000 mm
Height including railing	2.32 m



Load capacity	max. 150 kg
Number of rungs, incl. platform	5
Overall base width	0.68 m
Overall length	2.71 m
Platform height	1.32 m
Platform length	400 mm
Platform material	Aluminium ribbed plate
Platform width	400 mm
Standards	EN 131 professional
Stile depth	73 mm
Stile depth	58 mm
Stile depth steps/back stay	73mm / 58mm
Transport dimensions	approx. 2.710 mm × 680 mm × 210 mm
Tray	Aluminium
Tread depth	80 mm
Type rung/tread	Safer Step
Warranty	10 years
Weight	14.4 kg
Working height	3.32 m

ZARGES GmbH

Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 4/2/2026

Subject to change or error.