

# K 424 XC Mobile Box - 41814

The new K 424 XC combines the legendary quality of ZARGES cases with new mobility.

## Product description

- The K 424 XC has excellent mobility and ergonomics owing to its integrated wheels and pull-out handles (for order no. 41810-41814) or second sprung drop handle on the end face (for order no. 41815).
- All-round beading and corner beading offer additional stability, allowing the box to withstand a load of up to 50 kg despite its low weight.
- Stackability guaranteed through stacking corners made from impact-resistant plastic and integrated stacking elements in the support frame. Can also be stacked with containers in the ZARGES K 470 and Eurobox series.
- Can be fitted with an optional 125 mm wheel set or 220 mm off-road wheel set (for models with a volume of 60 litres and above) to improve its mobility on difficult terrain.
- Sturdy, mobile aluminium box in ZARGES quality, long service life, a reliable companion.
- Optimum mobility through integrated 50 mm castors and pull-out handle (Order No. 41810-41814) or second sprung drop handle on the end face (Order No. 41815).
- Extremely smooth-running due to special castors, ø



50 mm, made from polyurethane and polyamide.

- ZARGES Comfort fasteners with extremely long service life, fitted with plug locks.
- High load-bearing capacity of up to 50 kg despite the low dead weight.
- UN approval for the transportation of hazardous goods possible at additional charge.
- Optional wheel set 125 mm or off-road set 220 mm available for use in difficult terrain.
- Beading all round and corner beads for additional dimensional stability.
- A wide range of adjustable interior fittings ensure versatility.
- Peripheral foamed seal in the lid for protection against dust and splashwater.

## Hints and special features

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

## Product features

Colour of the stacking corners <b>Natural aluminium</b>	Corner beading <b>Yes</b>	Fasteners <b>Comfort fasteners</b>	Handles <b>Sprung drop handles</b>	Integrated wheels <b>Yes</b>
Internal dimensions L x W x H <b>750 mm × 635 mm × 410 mm</b>	Material <b>Aluminium</b>	Material of the stacking corners <b>Aluminium</b>	Max. gross weight dangerous goods permission <b>35 kg</b>	Outside dimensions max. L x W x H <b>800 mm × 685 mm × 485 mm</b>
Peripheral beading	Pull handle	Seal	Stacking corners	Total max. weight



Yes	2-section	foamed lid seal	Yes	35 kg
Volume	Weight	Wheel diameter		
195 l	12 kg	50 mm		