

## Varioflex B - 41936

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.

### Product description

- Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.
- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from extruded aluminium sections.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Ideal for applications in difficult terrain.

Complies with EN 131 Professional.

### Product features

Additional adjustment range on ladder section	0.4 m
Additional adjustment range on support section	1.3 m
Coating	natural
Connection Stile-Rung	flanged



Length excluding extension	1.8 m
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	6
Number of rungs	2 × 6
Pitch rung/tread	265 mm
Transport dimensions	1.850 mm × 600 mm × 140 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	12.5 kg
Working height	3 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 5/13/2026

Subject to change or error.