



ZARGES

Varioflex B - 41938

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.

Product description

- Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.
- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from extruded aluminium sections.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Ideal for applications in difficult terrain.

Complies with EN 131 Professional.

Product features

Additional adjustment range on ladder section 0.4 m	Additional adjustment range on support section 1.85 m	Coating natural	Connection Stile-Rung flanged	Length excluding extension 2.35 m
Load capacity	Material	Number of rungs	Number of rungs	Pitch rung/tread

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

www.zarges.com

zarges@zarges.de

Effective
2/12/2026

Subject to change or error.

1/2



max. 150 kg	Aluminium	8	2 x 8	265 mm
Transport dimensions 2.410 mm x 650 mm x 140 mm	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	Weight 15.5 kg
Working height 3.55 m				