

Combimaster X - 41941

Practical dual-function ladder that can be used as a single ladder or stepladder for flexible application.

Product description

- Practical dual-function ladder that can be used as a single ladder or stepladder for flexible application.
- Strong, steel joint bolted to the stiles.
- Self-locking.
- Can be used as either a single ladder or a stepladder.
- One ladder section with broad horizontal stabiliser bar.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Length as lean-to ladder	2.5 m
Length as stepladder	1.3 m
Load capacity	max. 150 kg
Material	Aluminium



Number of rungs	4
Number of rungs	2 × 4
Pitch rung/tread	265 mm
Standards	EN 131-4
Stile depth	58 mm
Transport dimensions	1.265 mm × 360 mm × 130 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	6 kg
Wide crosspiece	0.75 m
Working height as lean-to ladder	3.35 m
Working height as stepladder	2.55 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/18/2026

Subject to change or error.