

# Combimaster X - 41942

Practical dual-function ladder that can be used as a single ladder or stepladder for flexible application.

## Product description

- Practical dual-function ladder that can be used as a single ladder or stepladder for flexible application.
- Strong, steel joint bolted to the stiles.
- Self-locking.
- Can be used as either a single ladder or a stepladder.
- One ladder section with broad horizontal stabiliser bar.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Length as lean-to ladder <b>3.6 m</b>	Length as stepladder <b>1.85 m</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs <b>6</b>	Number of rungs <b>2 × 6</b>	Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131-4</b>
Stile depth <b>58 mm</b>	Transport dimensions <b>1.870 mm × 360 mm</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>



	× 130 mm			
Weight <b>8 kg</b>	Wide crosspiece <b>0.8 m</b>	Working height as lean- to ladder <b>4.4 m</b>	Working height as stepladder <b>3.1 m</b>	