



Mobile access steps with platform, single-sided access, with steel open-grid treads and platform - 41952

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.



Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.

Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7



Product features

| | |
|---------------------------------|----------------------------|
| Base | 0,82 m × 1,45 m |
| Coating | natural |
| Connection Stile-Rung | welded |
| Guardrail height | 1000 mm |
| Load capacity | max. 150 kg |
| Material | Aluminum/steel, galvanised |
| Number of rungs, incl. platform | 4 |
| Pitch rung/tread | 240 mm |
| Platform height | 0.96 m |
| Platform length | 800 mm |
| Platform width | 600 mm |
| Standards | EN 131-7 |
| Transport dimensions | 1.350 mm × 830 mm × 410 mm |
| Tread depth | 200 mm |
| Type rung/tread | Open-grid surface |
| Warranty | 10 years |
| Weight | 47.5 kg |
| Working height | 2.95 m |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/3/2026

Subject to change or error.