

Mobile access steps with platform, single-sided access, with steel open-grid treads and platform - 41954

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.



Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.

Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

Product features

| | | | | |
|---|--|---|------------------------------------|---|
| Base 0,93 m × 1,81 m | Coating natural | Connection Stile-Rung welded | Guardrail height 1000 mm | Load capacity max. 150 kg |
| Material Aluminum/steel, galvanised | Number of rungs, incl. platform 6 | Pitch rung/tread 240 mm | Platform height 1.44 m | Platform length 800 mm |
| Platform width 600 mm | Standards EN 131-7 | Transport dimensions 1.820 mm × 930 mm × 350 mm | Tread depth 200 mm | Type rung/tread Open-grid surface |
| Warranty 10 years | Weight 59.7 kg | Working height 3.45 m | | |