



## Mobile access steps with platform, single-sided access, with steel open-grid treads and platform - 41954

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.



### Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.

### Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7



## Product features

Base	0,93 m × 1,81 m
Coating	natural
Connection Stile-Rung	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	Aluminum/steel, galvanised
Number of rungs, incl. platform	6
Pitch rung/tread	240 mm
Platform height	1.44 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	1.820 mm × 930 mm × 350 mm
Tread depth	200 mm
Type rung/tread	Open-grid surface
Warranty	10 years
Weight	59.7 kg
Working height	3.45 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 4/19/2026

Subject to change or error.