ZARGES

DATA SHEET

Mobile access steps with platform, double-sided access, with steel open-grid treads and platform -

The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.



PRODUCT DESCRIPTION

- The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.

HINTS AND SPECIAL FEATURES

Double-sided handrail in accordance with EN 131-7 on access optional.
Complies with EN 131-7

PRODUCT FEATURES

Property	Value
Base	0,87 m × 2,06 m
Coating	natural
Connection Stile-Rung	welded
Guardrail height	1000 mm

Property	Value
Load capacity	max. 150 kg
Material	Aluminum / Steel, galvanised
Number of rungs, incl. platform	2 × 5
Number of treads	5
Pitch rung/tread	240 mm
Platform height	1.2 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	1.850 mm × 890 mm × 460 mm
Tread depth	200 mm
Type rung/tread	Open-grid surface
Warranty	10 years
Weight	70.1 kg
Working height	3.2 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 3



Handrail
SKU 41970



Pole barrier
SKU 41957



Tray
SKU 41967

SPARE PARTS 6



Castor, anti-static
SKU 803298



Push-on end cap
SKU 824409



Push-on end cap, antistatic
SKU 824475



Sprung castor for platform steps
SKU 802198



Sprung castor for platform steps
SKU 802199



User instructions label
SKU 800597

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 10/31/2026
Subject to change or error.