

Mobile access steps with platform, double-sided access, with steel open-grid treads and platform - 41963

The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.



Product description

- The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.

Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7



Product features

Base 0,87 m × 2,06 m	Coating natural	Connection Stile-Rung welded	Guardrail height 1000 mm	Load capacity max. 150 kg
Material Aluminum/steel, galvanised	Number of rungs, incl. platform 2 × 5	Number of treads 5	Pitch rung/tread 240 mm	Platform height 1.2 m
Platform length 800 mm	Platform width 600 mm	Standards EN 131-7	Transport dimensions 1.850 mm × 890 mm × 460 mm	Tread depth 200 mm
Type rung/tread Open-grid surface	Warranty 10 years	Weight 70.1 kg	Working height 3.2 m	