



Mobile access steps with platform, double-sided access, with steel open-grid treads and platform - 41963

The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.



Product description

- The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.

Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7



Product features

Base	0,87 m × 2,06 m
Coating	natural
Connection Stile-Rung	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	Aluminum/steel, galvanised
Number of rungs, incl. platform	2 × 5
Number of treads	5
Pitch rung/tread	240 mm
Platform height	1.2 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	1.850 mm × 890 mm × 460 mm
Tread depth	200 mm
Type rung/tread	Open-grid surface
Warranty	10 years
Weight	70.1 kg
Working height	3.2 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/18/2026

Subject to change or error.